



Referencia		Ø Nominal	Paso	Ø Bolas	Circuitos	Diámetros					Longitudes						Cargas		Rigidez	
Reference		Ø Nominal	Pitch	Ø Ball	Circuits	Diameters					Lengths						Loads		Rigidity	
Reference		Ø Nominal	Pas	Ø Billes	Circuits	Diamètres					Longueurs						Charges		Rigidite	
Riferimento		Ø Nominale	Passo	Ø Sfere	Circuiti	Diametri					Longhezze						Carichi		Rigidita	
Referenz		Ø Nenn	Steigung	Ø Kugel	Umläufe	Durchmesser					Längen						Tragzahl		Steifigkeit	
Tuerca única	Tuerca doble	d <sub>0</sub>	P <sub>ho</sub>	Dw	i	d <sub>3</sub>	D <sub>1</sub>	D <sub>4</sub>	D <sub>5</sub>	D <sub>6</sub>	L	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>7</sub>	L <sub>8</sub>	Dinámica	Stática	Husillo por metro	Tuerca doble
Single nut	Double nut																Dinamica	Estatic		
Ecrou simple	Ecrou double	d <sub>0</sub>	P <sub>ho</sub>	Dw	i	d <sub>3</sub>	D <sub>1</sub>	D <sub>4</sub>	D <sub>5</sub>	D <sub>6</sub>	L	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>7</sub>	L <sub>8</sub>	Dynamique	Statique	Vis par mètre	Ecrou double
Chiocciola singola	Doppia Chiocciola																Dinamica	Statica		
Einzel - Mutter	Doppel - Mutter	d <sub>0</sub>	P <sub>ho</sub>	Dw	i	d <sub>3</sub>	D <sub>1</sub>	D <sub>4</sub>	D <sub>5</sub>	D <sub>6</sub>	L	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>7</sub>	L <sub>8</sub>	Dynamische	Statische	Spindel per Meter	Doppel - Mutter
																	Cam (KN)	Coam (KN)		
1.050.05.4.4	2.050.05.4.4	50	5	3,969	4	47,4	75	93	11	110	104	10	63	7	16	85	35	103,7	389	1100
1.050.05.4.5	2.050.05.4.5				5								68				42,4	129,6		1400
1.050.05.4.6	2.050.05.4.6				6								73				49,6	155,5		1650
1.050.10.7.3	2.050.10.7.3	50	10	7,144	3	45,14	75	93	11	110	143	20	83	7	16	85	56,8	123	370	1000
1.050.10.7.4	2.050.10.7.4				4								94				72,7	164		1300
1.050.10.7.5	2.050.10.7.5				5								105				88	205		1600
1.050.10.7.6	2.050.10.7.6				6								116				103	246		1800
1.050.12.8.3	2.050.12.8.3	50	12	7,938	3	44,58	75	93	11	110	176	20	103	7	16	85	65	135	364	1000
1.050.12.8.4	2.050.12.8.4				4								116				83,2	180		1300
1.050.12.8.5	2.050.12.8.5				5								128				100,8	225		1600
1.050.15.8.3	2.050.15.8.3	50	15	7,938	3	44,58	75	93	11	110	198	20	115	7	16	85	62,2	126,8	364	1000
1.050.15.8.4	2.050.15.8.4				4								131				79,7	169,1		1300
1.050.15.8.5	2.050.15.8.5				5								147				96,6	211,4		1600
1.050.16.8.3	2.050.16.8.3	50	16	7,938	3	44,58	75	93	11	110	203	20	115	7	16	85	62,2	126,8	364	1000
1.050.16.8.4	2.050.16.8.4				4								132				79,7	169,1		1300
1.050.16.8.5	2.050.16.8.5				5								149				96,6	211,4		1600
1.050.20.8.3	2.050.20.8.3	50	20	7,938	3	44,58	75	93	11	110	228	20	133	7	16	85	62	126,4	364	1000
1.050.20.8.4	2.050.20.8.4				4								155				79,4	168,6		1300
1.050.20.8.5	2.050.20.8.5				5								176				96,2	210,7		1600
1.050.25.8.3	2.050.25.8.3	50	25	7,938	3	44,58	82	100	11	118	232	25	119	7	16	92	69,1	150	364	1050
1.050.25.8.4	2.050.25.8.4				4								144				88,6	200		1375
1.050.30.8.2	2.050.30.8.2	50	30	7,938	2	44,58	82	100	11	118	200	25	103	7	16	92	48,5	99,2	364	750
1.050.30.8.3	2.050.30.8.3				3								133				68,7	148,8		1050
1.050.40.8.2	2.050.40.8.2	50	40	7,938	2	44,58	82	100	11	118	228	25	119	7	16	92	47,7	98	364	750
1.050.40.8.3	2.050.40.8.3				3								159				67,6	147		1050
1.050.50.8.2	2.050.50.8.2	50	50	7,938	2	44,58	82	100	11	118	283	25	143	7	16	92	46,8	96,5	364	750